60'-0"
14'-8"
12'-2"
17'-2"
16'-0"
RAILING
STEP(S) PER GRADE
DECK
PPT WOOD
(2)2X10 BEAM
3J
(3)2-8X5-2
3J
7'-4"
7'-4"
3'-0"
3'-2"
3'-2"
3'-2"
PRE-FAB TRUSSES @ 24" O.C. ABOVE, TYP.
3-0 SCREEN
RAILING
PRE-FAB TRUSSES @ 24" O.C. ABOVE, TYP.
(2)2X10 BEAM
SCREENED PORCH
PPT WOOD
(2)2X4
2-8X5-2 TEMPERED
3-0X6-8 FRENCH
2-8X5-2 TEMPERED
(2)2X4
ENGINEERED GIRDER TRUSS
14'-0"
(2)2X4
12'-2 1/2"
2J
ENGINEERED GIRDER TRUSS
6"X6" LOAD BEARING POSTS
16'-6"
16'-4"
5'-7"
5'-4"
5'-7"
8'-4"
8'-0"
CONTINUOUS ENGINEERED LVL BEAM
MASTER BEDROOM
TRAY CEILING
DINING
(2)2-8X5-2
7'-0"
2J
3-0X6-8 15 LITE W/TRANSOM
(2)2X12 BEAM
3-0X6-8 15 LITE W/TRANSOM
2'-0"
(2)2X4
(2)2X4
PRE-FAB VENTED GAS FIREPLACE
(2)2-8X5-2 TEMPERED
2J
2J
6-0
CLOSET
BEDROOM 2
11'-4"
32"X32" ATTIC ACCESS
4'-0"
11'-4 1/2"
3-0
SD
3-0 C.O.
3-0 C.O.
3-0 C.O.
CLOSET
CLOSET
6'-4"
4'-10"
3'-9"
4'-10"
45" HIGH WALL W/EXTENDED CAP
DW
8'-10"
3'-8 1/2"
16'-6"
KITCHEN
GREAT ROOM
CATHEDRAL CEILING
20'-4 1/2"
4'-0"
4'-0"
4'-0"
OVERHANG
15'-1"
4'-0"
11'-4 1/2"
BATH
3-0
1-6
2'-2"
LINEN
6'-1"
OVER-SIZED TUB
4-0X1-0 TRANSOM
2J
2J
40"X72" TUB
2-10
6'-2"
6'-2"
BATH
(2)2-4X4-2 TEMPERED
2J
MOUNT MINIMUM 2.5 LB. CLASS ABC - DRY CHEMICAL PORTABLE FIRE EXTINGUISHER INSIDE PANTRY
3'-1"
PRE-FAB TRUSSES @ 24" O.C. ABOVE, TYP.
CM
SD
2-10
SHOWER
1-6
LINEN
2'-1"
4'-6"
4'-6"
5'-7"
2-0X2-0 FIXED
3'-9"
1'-10"
FLUSH REF.
4-0 OPENING
SD
BEDROOM 3
MECHANICAL
WH
D
E
SINK
4-0
2'-10"
2-0
2'-8"
CLOSET
11'-4"
3-0
6'-8"
LNDRY
14'-0"
1'-0 1/2"
2-8X4-2
PRE-FAB TRUSSES @ 24" O.C. ABOVE, TYP.
2-8
PANTRY
6'-4 1/2"
1'-0 1/2"
4'-0"
4'-1"
3-0 PKT.
FOYER
6'-1"
3-0 PKT.
OFFICE
9'-4"
8'-8"
2'-1"
4'-1"
4'-0"
11'-4 1/2"
20 MINUTE FIRE RATED 3-0 DOOR
BLOCKING FOR FUTURE NETWORKING
3-0X6-8 W/12" SDLTS & TRANSOM
(2)2X4
2J
2J
2J
(2)2-8X5-2
2J
2J
(2)2-8X5-2
2J
3'-0"
8'-0"
5'-0"
8'-0"
8'-0"
ENGINEERED GIRDER TRUSS
(2)2X4
3-0X6-8 9 LITE
1/2" GYPSUM BOARD ATTACHED TO WALLS 5/8" TYPE-X GYPSUM BOARD ATTACHED TO CEILING
PRE-FAB TRUSSES @ 24" O.C.
PORCH
BRUSH FINISH CONCRETE
(2)2X4
(2)2X10 BEAM
10"X10" LOAD BEARING POSTS ON 16"X16" CONCRETE PIER WRAPPED W/FAUX STONE
STEP(S) PER GRADE
2-CAR GARAGE
ELECTRIC METER
4" CONCRETE SLAB ON 4" GRAVEL BASE W/WWM OR FIBERMESH REINFORCING AND POLY VAPOR BARRIER
25'-4"
RV PLUG
PRE-FAB TRUSSES @ 24" O.C. ABOVE, TYP.
SLOPE FLOOR
9'-0X8'-0 OVERHEAD GARAGE DOOR W/ENGINEERED LVL HEADER ABOVE
9'-0X8'-0 OVERHEAD GARAGE DOOR W/ENGINEERED LVL HEADER ABOVE
3J
3J
3J
3J
ELECTRICIAN TO INSTALL ALL BOXES FOR NETWORKING
37'-0" MAIN ROOF SPAN
40'-0"
24'-8"
7'-0"
5'-0"
10'-0"
7'-0"
15'-0"
30'-0"
32'-0"
15'-0"
44'-0"
13'-0"
2'-0"
6'-0"
18'-0"
24'-0"
24'-0"
26'-0"
21'-10"
4'-2"
2'-2"
6'-6"
6'-8"
4'-2"
7'-10"
12'-4"
7'-10"
28'-0"
16'-0"
16'-0"
60'-0"